






ULTRA Anchor Selection Table

RECOMMENDED ULTRA ANCHOR WEIGHT	SAIL BOAT		POWER BOAT			MULTIHULL			RECOMMENDED NOMINAL CHAIN SIZE	RECOMMENDED SWIVEL
	 MONO-HULL		 HIGH PROFILE	 LOW PROFILE		 SAIL	 POWER			
	BOAT WEIGHT	BOAT LENGTH	BOAT WEIGHT	BOAT LENGTH	BOAT LENGTH	BOAT WEIGHT	BOAT LENGTH	BOAT LENGTH		
	lbs	feet	lbs	feet	feet	lbs	feet	feet	inches	#
UA 5/11	2 205	17	2 425	17	19	1 543	14	15	3/16"	UFS 06 - 12
UA 8/18	4 410	23	4 850	24	26	3 086	20	21	1/4"	UFS 06 - 12
UA 12/26	8 380	30	9 260	31	33	5 950	26	27	1/4"	UFS 06 - 12
UA 16/35	13 890	35	15 210	36	40	9 920	31	32	1/4" - 5/16"	UFS 08 - 21
UA 21/46	22 490	41	24 690	43	47	16 100	36	38	5/16"	UFS 08 - 21
UA 27/60	32 190	47	35 270	48	53	23 150	41	43	5/16" - 3/8"	UFS 10 - 35
UA 35/77	47 400	52	51 800	54	60	34 400	45	48	3/8"	UFS 10 - 35
UA 45/100	66 140	58	72 530	60	66	47 620	51	53	3/8" - 1/2"	UFS 13 - 60
UA 60/132	94 800	66	103 830	68	74	68 340	58	60	1/2"	UFS 13 - 60
UA 80/176	139 880	73	152 120	75	83	100 100	63	67	1/2"	UFS 16 - 100
UA 100/220	187 000	80	205 000	83	91	134 000	70	73	9/16"	UFS 16 - 100
UA 130/290	271 000	90	298 000	93	102	196 000	78	82	9/16" - 5/8"	UFS 20 - 160
UA 160/350	384 000	100	421 000	103	113	276 000	86	91	5/8"	UFS 20 - 160
UA 200/440	578 000	113	633 000	116	128	419 000	98	103	11/16"	UFS 26 - 250
UA 250/550	882 000	129	966 000	133	146	639 000	111	117	3/4"	UFS 26 - 250
UA 300/660	1 213 000	144	1 323 000	149	163	882 000	125	131	7/8"	UFS 32 - 360
UA 360/800	1 675 000	164	1 830 000	169	186	1 213 000	142	150	15/16"	UFS 32 - 360



Scan me

CAUTION

- The ULTRA Anchor is designed to handle extremely heavy loads and caution is advised when handling.
- All materials have resistance limits, the use of high powered engines to free an anchor may deform it and/or cause damage to vessel.
- It is recommended to use a trip line or an ULTRA Anchor Ring to recover an anchor stuck under an obstruction.

ULTRA ANCHOR WARRANTY

- Select the largest ULTRA Anchor that will meet both the vessel's weight and length criteria.
- Users may select the next smaller size, depending on the type of anchoring they do and/or cruising area.
- ULTRA Anchors are warranted for lifetime based on these recommendations.

COMMENTS

- When selecting ULTRA Anchors in excess of 100 kg or 220 lbs. please consult Llyods or a comparable certification society. The listed values should be used for preliminary selection only.
- ULTRA Anchors work well as bow and stern anchors on horizontal roller assemblies, they are not suitable for vertical or straight hawse holes.
- It is recommended to use an ULTRA Flip Swivel or other suitably strong stainless steel connector.

Ultra Marine West
HOME OF THE ULTRA ANCHOR

ULTRA Marine West INC,
3774 SW 30TH AVENUE
FORT LAUDERDALE, FL 33312
sales@ultramarinewest.com
(954) 928-8101